

# Quanta 6 Q6-28

|                                  |  |
|----------------------------------|--|
| Description                      | Quanta 6 Q6-28, 6 GHz point-to-point unit, net throughput up to 650 Mbps, integrated dual-pol antenna, 28 dBi, 5x5 deg |
| Net throughput                   | up to 650 Mbps   |
| Recommended distances            | up to 80 km  |
| Radio technology                 | MIMO 2x2 (SC-FDE)  |
| Modulation coding schemes        | from QPSK 1/4 to QAM256 7/8  |
| Transmit power                   | from -10 to 27 dBm*, step 1 dBm  |
| Receiver sensitivity             | down to -101 dBm   |
| Frequency range                  | 6000-6425 MHz  |
| Channel width                    | 3.5, 5, 7, 10, 14, 15, 20, 28, 30, 40, 50, 56 MHz  |
| Center frequency adjustment step | 1 MHz  |
| Duplex scheme                    | TDD  |
| Antenna                          | 28 dBi   |
| Wired Interfaces                 | 1x Combo port GigabitEthernet/SFP  |

\*May be limited by regional EIRP restrictions

## Quanta 6 Q6-28

|                     |   |
|---------------------|---|
| Consumption         | up to 15 W  |
| Power options       | 90-240 VAC ~ @ 50/60 Hz, +-43.56 VDC  |
| Outdoor Unit (ODU)  | 600 x 600 x 68 mm, 5.8 kg   |
| Part Number Example | Q6-28   |
| Packing List        | <ul style="list-style-type: none"> <li>- Outdoor unit Q6-28 - 1 pcs.</li> <li>- Power Supply IDU-CPE-G(24W) - 1 pcs.</li> <li>- Power Cord - 1 pcs.</li> <li>- Cable Gland V1 - 1 pcs.</li> <li>- Cable Gland V2 - 1 pcs.</li> <li>- Standard RJ-45 connector - 1 pcs.</li> <li>- Shielded RJ-45 connector - 1 pcs.</li> <li>- RJ-45 Plug Cap - 1 pcs.</li> <li>- MONT-KIT-85S Mounting kit - 1 pcs.</li> <li>- Quick Start Guide - 1 pcs.</li> </ul> |



# Quanta 6 Q6-28

## Features

### RADIO

- ▶ DFS
  - ETSI/FCC, including radar detection (including off-channel CAC) and adaptivity
- ▶ Automatic Bitrate Control
- ▶ Automatic Transmit Power Control
- ▶ Channel Time Adjustment

### NETWORKING

- ▶ Built-in full-fledged L2 switch supporting
- ▶ Transparent L2 transport for Ethernet traffic

### MANAGEMENT FEATURES

- ▶ Various Management Protocols: HTTP, SSH, HTTPS, Telnet, SNMP v1/2c/3 (MIB-II and proprietary MIBs)
- ▶ Graphical User Interface
- ▶ LED Indication: power status, wireless and wired link status, signal level
- ▶ Antenna alignment tool
- ▶ Automatic software update
- ▶ Online monitoring with proprietary EMS NEXT

### QUALITY-OF-SERVICE

- ▶ 8 priority queues
- ▶ IEEE 802.1p support
- ▶ IP DiffServ support

# Quanta 5 Q5-28

## Features

### ENVIRONMENTAL

- ▶ Outdoor Units:
  - operating temperature range  $-40..+60$  °C, (can be extended to  $-55..+60$  °C, models with "t" index in PN), 100% humidity, condensing
  - IP66/IP67 compliant water and dust protection
- ▶ Indoor Unit:  $0..+40$  °C, 95% humidity, non-condensing

### SECURITY FEATURES

- ▶ Storm/flood protection
- ▶ Password protection
- ▶ Secure command-line access via SSH protocol

### MAC

- ▶ VLAN 802.1q

### STANDARD COMPLIANCE

- ▶ Safety:
  - EN/IEC 62368-1:2014, UL 62368-1:2014
- ▶ Radio:
  - EN 301 893 v.2.1.1, EN 302 502, v.2.1.1, FCC part 15.407
- ▶ EMC:
  - ETSI EN 301 489-1, ETSI EN 301 489-17, FCC Part 15 Class B
- ▶ RoHS:
  - RoHS3 Directive 2015/863/EU (pending)

# Quanta 6 Q6-28

## Radiation diagram

