

Astrawireless Quasar Qsr5-26

PRODUCT DATASHEET

Description Quasar Qsr5-26, 5 GHz point-to-point unit with 26 dBi removable antenna

Antenna Removable dual-pol antenna, 26 dBi, 8x8°

Recommended distance up to 20 km

Frequency range 4900-6060 MHz

Channel width 20, 40, 80, 160 MHz

Net throughput up to 2100 Mbps in 160 Mhz
up to 1100 Mbps in 80 MHz

Transmit power up to 30 dBm**, step 1 dBm

Receiver sensitivity down to -93 dBm

Center frequency adjustment step 1 MHz

Multiple access Polling, TDD*



*Roadmap

**May be limited by regional EIRP restrictions

Astrawireless Quasar **Qsr5-26**

PRODUCT DATASHEET

Wired Interfaces 1x 2,5 Gigabit Ethernet port (RJ45),
1x 10 Gigabit SFP, 1x DC IN, 1x Sync

Consumption Up to 30 W

Power options 90-240 VAC ~ @ 50/60 Hz, +-43.56 VDC

Part Number Example Qsr5-26

Form Factor and Dimensions **Outdoor Unit (ODU)**
Ø430 x 150 mm, 2.3 kg

Indoor Unit IDU-CPE-G (56W)
137,5 x 62,5 x 33 mm, 0.24 kg

Packing List

- Outdoor unit Qsr5-26 - 1 pcs
- Power Supply IDU-CPE-G(56W) - 1 pcs
- Power Cord - 1 pcs
- Cable Gland for RJ-45 - 2 pcs
- Cable Gland for SFP - 1 pcs
- Standard RJ-45 connector - 1 pcs
- Shielded RJ-45 connector - 1 pcs
- RJ-45 Plug Cap - 1 pcs
- MONT-KIT-85 Mounting kit - 1 pcs
- Quick Start Guide - 1 pcs

RADIO FEATURES

- **Radio technology**
MIMO 2x2, OFDM 64/128
- **Automatic Bitrate Control**
Automatic Transmit Power Control
Automatic Distance Learning
- **Modulation types**
From BPSK 1/2 to QAM 4096 5/6
- **Channel Time Adjustment**
Channel testing tools
- **Voice/RTP Aware Superpacketing**
- **Spectrum Analyzer mode**

Wide range of network settings

Multi-kilometer gigabit backhaul

Easy operation due to automatic control options

NETWORKING FEATURES

- **MAC**
Full-fledged 2nd layer switch
VLAN 802.1q
- **Quality of Service**
IEEE 802.1p support
8 priority queues
- **Proprietary MINT network protocol**
Pseudo-radio interface
Own switch group system
- **DHCP-client**



MANAGEMENT AND SECURITY

■ Various Management Protocols HTTP, HTTPS, SSH, Telnet, SNMP v1/2c/3 (MIB-II and proprietary MIBs)	■ Antenna alignment tool Automatic software update Online monitoring with EMS NEXT WEB GUI	■ Safety & Security Storm/flood protection Password protection Secure CLI access via SSH protocol	■ LED Indication Power status Wired link status
--	--	--	---

STANDARD COMPLIANCE*

■ Radio ETSI EN 301 893 v.2.1.1 ETSI EN 302 502 v.2.1.1 FCC part 15.407	■ EMC ETSI EN 301 489-1 v.2.1.1 ETSI EN 301 489-17 v.3.1.1 FCC Part 15 Class B	■ Safety EN 62368-1:2014+A11:2017 UL 62368-1:2014 EN 62311:2008 RoHS3 EN IEC 63000:2018	■ Lightning protection IEC 61000-4-2: +/-4kV (contact discharge), +/-8kV (air discharge) IEC 61000-4-4: +/-0.5kV IEC 61000-4-5: +/-1kV (line-to-ground), +/-0.5kV (line-to-line)
--	---	---	--

OPERATION OPTIONS

■ Power options 90–240 VAC @ 50/60 Hz ±43.56 VDC 802.3at or Proprietary PoE	■ Outdoor Unit environmental conditions -40..+60°C, can be extended to -55..+60°C (models with "t" index in PN) 100% humidity, condensing	■ Indoor Unit environmental conditions 0..+40°C 95% humidity, non-condensing
--	---	--

*Pending



Astra Wireless Technology. All rights reserved.
www.astrawireless.net
sales@astrawireless.net