

Astrawireless Quasar Qsr5-26

PRODUCT DATASHEET

Description

Quasar Qsr5-26, 5 GHz
point-to-point unit with
26 dBi removable antenna

Antenna

Removable dual-pol
antenna, 26 dBi, 8x8°

Recommended distance

up to 20 km

Frequency range

4900-6060 MHz

Channel width

20, 40, 80, 160 MHz

Net throughput

up to 2100 Mbps in 160 Mhz
up to 1100 Mbps in 80 MHz

Packet performance

Up to 500 000 pps

Transmit power**

up to 30 dBm, step 1 dBm

Receiver sensitivity

down to -93 dBm

Center frequency adjustment step

1 MHz



*Roadmap

**May be limited by regional EIRP restrictions

Astrawireless Quasar Qsr5-26

PRODUCT DATASHEET

Wired Interfaces

1x 2,5 Gigabit Ethernet port (RJ45),
1x 10 Gigabit SFP, 1x DC IN, 1x Sync

Multiple access

Polling, TDD

Consumption

Up to 30 W

Power options

90-240 VAC ~ @ 50/60 Hz, +-43.56 VDC

Part Number Example

Qsr5-26

Form Factor and Dimensions

Outdoor Unit (ODU)
Ø430 x 150 mm, 2.3 kg

Indoor Unit IDU-CPE-G (56W)
137,5 x 62,5 x 33 mm, 0.24 kg

Packing List

- Outdoor unit Qsr5-26 - 1 pcs
- Power Supply IDU-CPE-G(56W) - 1 pcs
- Power Cord - 1 pcs
- Cable Gland for RJ-45 - 2 pcs
- Cable Gland for SFP - 1 pcs
- Standard RJ-45 connector - 1 pcs
- Shielded RJ-45 connector - 1 pcs
- RJ-45 Plug Cap - 1 pcs
- MONT-KIT-85 Mounting kit - 1 pcs
- Quick Start Guide - 1 pcs

RADIO FEATURES

- **Radio technology**
MIMO 2x2, OFDM 64/128
- **Automatic** Bitrate Control
Automatic Transmit Power Control
Automatic Distance Learning
- **Modulation types**
From BPSK 1/2 to QAM 4096 5/6
- Channel Time Adjustment
Channel testing tools
- Voice/RTP Aware Superpacketing
- Spectrum Analyzer mode

Wide range of
network settings

■ Multi-kilometer
gigabit backhaul

■ Easy operation due to
automatic control options

NETWORKING FEATURES

- **MAC**
Full-fledged 2nd layer switch
VLAN 802.1q
- **Quality of Service**
IEEE 802.1p support
8 priority queues
- Proprietary MINT network protocol
Pseudo-radio interface
Own switch group system
- DHCP-client



MANAGEMENT AND SECURITY

■ Various Management Protocols HTTP, HTTPS, SSH, Telnet, SNMP v1/2c/3 (MIB-II and proprietary MIBs)	■ Antenna alignment tool Automatic software update Online monitoring with EMS NEXT WEB GUI	■ Safety & Security Storm/flood protection Password protection Secure CLI access via SSH protocol	■ LED Indication Power status Wired link status
--	--	--	---

STANDARD COMPLIANCE*

■ Radio ETSI EN 301 893 v.2.1.1 ETSI EN 302 502 v.2.1.1 FCC part 15.407	■ EMC ETSI EN 301 489-1 v.2.1.1 ETSI EN 301 489-17 v.3.1.1 FCC Part 15 Class B	■ Safety EN 62368-1:2014+A11:2017 UL 62368-1:2014 EN 62311:2008 RoHS3 EN IEC 63000:2018	■ Lightning protection IEC 61000-4-2: +/-4kV (contact discharge), +/-8kV (air discharge) IEC 61000-4-3: +/-0.5kV IEC 61000-4-4: +/-1kV (line-to-ground), +/-0.5kV (line-to-line)
--	---	---	--

OPERATION OPTIONS

■ Power options 90–240 VAC @ 50/60 Hz ±43.56 VDC 802.3at or Proprietary PoE	■ Outdoor Unit environmental conditions -40..+60°C, can be extended to -55..+60°C (models with "t" index in PN) 100% humidity, condensing Dust and water protection IP66, IP67 Wind load 160 km/h, operational; 200 km/h, survival	■ Indoor Unit environmental conditions 0..+40°C 95% humidity, non-condensing
--	--	--


*Pending




Astra Wireless Technology. All rights reserved.
www.astrawireless.net
sales@astrawireless.net

Radiation pattern


E-plane H-pol




E-plane V-pol



H-plane H-pol



H-plane V-pol



Astrawireless

Astrawireless Technology. All rights reserved.
www.astrawireless.net
sales@astrawireless.net